24MY ZM OUTLANDER PLUG-IN HYBRID INSPECTION AND MAINTENANCE SCHEDULE

For items which indicate both distance and time (in months), the inspection should be made at whichever (distance or time) comes first. Maintenance operation code

Inspection L:Lubrication R:Replace or change															
		Service Intervals (Odometer reading or months, whichever occurs first)													
Items Months		12	24	36	48	60	72	84	96	108	120	132	_	156	168
Odometer Reading	× 1000 km	15	30	45	60	75	90	105	120	135	150	165	180	195	210
OPERATIONS INSIDE THE ENGINE COMPARTMENT															
Check drive belt for cracks, fraying, wear, and adjust its tension		- 1		- 1	- 1	Ţ	I	I	I	- 1	I	I	1		I
Replace spark plugs							R						R		
Check valve clearance (* Denotes audible check only) *4		l*	l*	*	*	l*	- 1	l*	l*	l*	l*	l*	I	*	l*
Check radiator hoses for damage and proper connection		-	I	- 1	- 1	ı	- 1	I	I	- 1	I	I	I		I
Check engine coolant level in reservoir		I	- 1	- 1	- 1	I	- 1	- 1	I	-	I	- 1	I	1	- 1
Change engine coolant *2									R					R	
Check air cleaner element for clogging and damage Normal usage Severe usage		-	- 1	- 1	- [ı	- 1	- 1	I	1		- 1	1	I	Ι
						I: Ev	ery 7,5	500km	or ever	y 6 mc	nths	7			
Normal usage	Normal usage			R			R			R			R		
Replace air cleaner element Severe usage															
Check fluid level in brake reservoir		- 1	I	I	- 1	I	I	I	I	- 1	I	I	ı	I	Ι
Change brake fluid			R		R		R		R		R		R		R
Check battery condition (Except drive battery)		- 1	I	I	I	I	Ι	I	I	I	I	I	ı	I	Ι
Check high voltage cable for damage and proper connection			ı		I		ı		I		ı		ı		Ι
Check front motor cooling oil leakage		I	- 1	Ι	- 1	I	Ι	- 1	I	- 1	- 1	I	- 1	Ι	Ι
Check rear motor coolant level in reservoir		- 1	I	I	I	I	Ι	I	I	I	I	I	ı	I	Ι
Change rear motor coolant		R: Every 400,000km or every 20years													
Replace fuel filter											R				
OPERATIONS UNDER THE VEHICLE															
Check suspension system for damage and looseness Normal usage Severe usage	Normal usage	I	I	Ι	I	I	I	I	I	I	I	I	ı	I	Ι
	Severe usage				_	I: Ev	ery 7,5	500km	or ever	y 6 ma	nths				
Check suspension arm ball joints for play, and dust covers for damage	Normal usage	1	I	I	- 1	I	I	I	I	- 1	I	I	ı	I	Ι
	Severe usage	l: Every 7,500km or every 6 months													
Check driveshaft boots for damage	Normal usage	1	I	I	- 1	I	I		I	- 1	I	I	ı	I	Ι
	Severe usage	I: Every 7,500km or every 6 months													
Check steering linkage for damage and loose connections	Normal usage	_	I	Ι	I	Π	Ι	I	I	ı	I	I	Ι	П	Π
	Severe usage	I: Every 7,500km or every 6 months													
Check front transaxle for oil leakage (In case of leakage, check the oil level)		- 1	I	I	- 1	I	I	I	I	- 1	I	I	- 1	I	Ι
Check rear transaxle for oil leakage (In case of leakage, check the oil level)		I	ı	I	ı	ı	I	ı	I	ı	ı	ı	Ι	T	Ι
Change front transaxle oil *3	Normal usage										R				
	Severe usage		R		R		R		R		R		R		R
Channel 1997	Normal usage										R				
Change rear transaxle oil *3 Severe usag			R		R		R		R		R		R		R
Check exhaust pipe connections for gas leakage, and check pipe installation		I	I	I	I	I	I	I	ı	I	I	I			

^{*1} These maintenance items and intervals are recommended for reliable vehicle operation. The owner need not perform such maintenance in order to maintain the emission warranty or manufacturer recall liability. Other maintenance items and intervals are required

^{*2} Use only MITSUBISHI MOTORS Genuine Super Long Life Coolant Premium or equivalent with proper mixture ratio of 50% anti-freeze and 50% demineralized or distilled water. Mixing any other type of coolant or the use of non-distilled water will reduce the life expectancy of the factory-fill coolant.

^{*3} If towing a trailer, using a camper or a car-top carrier or driving on rough or muddy roads, change (not just inspect) oil at every 30,000 km or12months.

^{*4} If found any abnormal noise is heard from the valve train any time, please check the valve clearance.

			Service Intervals (Odometer reading or months, whichever occurs first)													
Items			12	24	36	48	60	72	84	96	108	120	132	144	156	168
	Odometer Reading	× 1000 km	15	30	45	60	75	90	105	120	135	150	165	180	195	210
OPERATIONS INSIDE THE VEHICLE																
Check l	orake pedal for free play			ı	_	_	ı	I	ı	I		ı	I	ı		_
Replace air purifier filter	Normal usage	R	R	R	R	R	R	R	R	R	R	R	R	R	R	
replace all partier filter		Severe usage	R: More frequently													
Check operation of all functions including wipers and lights		I	I	- 1	I	- 1	- 1	- 1	I	- 1	- 1	- 1	- 1		L	
OPERA	TIONS OUTSIDE THE VEHICLE															
Check \	vheel alignment and report any abnormal tyre wear		I	I	- 1	I	ı	ı	ı	I	- 1	- 1	ı	ı		
Check t	yre pressures		I	I	I	I	- 1	I	- 1	I	1	- 1	- 1	ı		
Check front and rear wheel bearings for play	Normal usage	1	I	- 1	I	I	I	ı	I		ı	ı	ı			
CHECK	Sever	Severe usage	I: Every 7,500km or every 6 months													
Check brake hoses and pipes for leakage	Normal usage	-	I	I	I	ı	ı	ı	I	1	- 1	ı	ı			
	Severe usage	I: Every 7,500km or every 6 months														
ICheck brake pads and discs for wear	Normal usage	- 1	I	- 1	I	I	I	I	I	I	I	I	I			
	Severe usage	I: Every 7,500km or every 6 months														
Check fuel hoses and pipes for leakage or deterioration		I	I	I	I	I	I	ı	I	ı	I	I	I			
OPERA	TIONS AFTER ENGINE IS WARMED UP			_			_									
Change engine oil	Normal usage	R	R	R	R	R	R	R	R	R	R	R	R	R	R	
	Severe usage	R: Every 7,500km														
Replace engine oil filter	Normal usage	R	R	R	R	R	R	R	R	R	R	R	R	R	R	
	Severe usage	R: Every 7,500km														
Check 6	xhaust gas recirculation (EGR) system		I	I	I	I	I	I	I	I	ı	- 1	I	- 1		
OTHER																
_	ody condition for damage		I	I	- 1	I	I	I	I	I	I	I	I	I		- 1
	naintenance service interval reminder		ı	I	ı	I	ı	ı	ı	I	1	I	I	I		I
Road to	est		- 1	- 1	- 1	I	- 1	- 1	- 1	I		- 1	I	- 1	'	1 1

NOTE:

"Severe usage" specifications apply to only vehicles used under severe operating conditions.

Severe operating conditions include the following cases :

- (1) Driving in dusty conditions or exposure to salty air or brine.
- (2) Driving on rough roads, on submerged roads, or hilly areas.
- (3) Driving in cold zones.
- (4) Engine idling for a long time or short-distance travel during cold weather.
- (5) Frequent, sudden application of brakes.

- (6) Towing of a trailer.
- (7) Use as a taxi or as a rent-a-car.
- (8) More than 50% of operation time in heavy city traffic in hot temperatures of 32° C or higher.
- (9) More than 50% of operation time at speeds of 120km/h or higher in hot temperatures of 30° C or higher.
- (10) Operation under excessive load.